CWRU
WRITTEN PROGRAM
FOR BENZENE

29 CFR 1910.1028

Written 09/1999
Revised 08/2011

A. OSHA defines a regulated area as "any area where airborne concentrations of benzene exceed or can reasonably be expected to exceed, the permissible exposure limits..."

B. Access to labs determined to be regulated areas must be restricted to designated personnel so the number of people exposed to benzene is minimized.

VI. Control Methods

A. Exposure to benzene in the lab must be avoided to prevent adverse health effects, especially exposure via inhalation and dermal absorption. Established engineering controls, personal protective equipment, and work practices used to reduce benzene exposure must be included in the lab's Chemical Hygiene Plan.

B. Engineering controls

1. Engineering controls must be established first to reduce benzene exposure to the lowest possible level; then, if still warranted personal protective equipment (PPE) must be used. The necessary types of engineering controls and PPE are lab-specific and must be included in the lab's Chemical Hygiene Plan.

2. Fume hoods are provided in most labs as the most common engineering control. Additional ventilation and containment may be required depending on the procedures performed. Such risk assessments must be determined on an individual basis.

C. Personal protective equipment (PPE)

1. The minimum PPE requirement when working in a lab includes goggles, lab coat, and gloves. Additional PPE with more protection may be required depending on the procedures performed.

2. When ordering the appropriate PPE for a lab, chemical protective clothing charts must be reviewed since PPE material formulations vary by supplier.

3. If respirators are deemed necessary, EHS will supply them in accordance with 29 CFR 1910.134 and 29 CFR 1910.1028 (g).

4. PPE must be provided by the employer to the employee free of charge.

D. Laboratory Work Practices

1. Benzene solutions must be used in fume hoods as the designated work area.

2. Eyewash stations and safety showers must be within the immediate work area.

3. Gloves, goggles, and lab coats must be worn when working with benzene. Additional PPE may be required depending on the procedure.

4.

2. If exposures are above the AL in a particular work area, the employees in that area must be trained annually.

3. Training is conducted by EHS.

B. Contents

1. Presence of chemicals

2. Health hazards

3. Work practices

4. Emergency procedures

5. Engineering controls & personal protective equipment

6. Labels

7. Material Safety Data Sheets

8. Summary of the 29 CFR 1910.1028

9. Medical Surveillance Program

IX. Medical Surveillance Program

A. General cp

am`l

1. Without c ost to th e e mploy es

1. The employer must provide to the physician a copy of 29 CFR 1910.1028, a description of the employee's duties, the determined exposure level, and personal protective equipment used.

2. The employer must provide the employee a copy of the physician's written opinion and results within 15 days of the exam. The written opinion from the physician to the employer must pertain only to the employee's ability to work with benzene.

X. Recordkeeping

A. Exposure Results

1. The records must include the results' number, date, duration, analytical method, the procedure performed while samples were collected, and any personal protective equipment worn by person monitored. It must also include the person's name, social security number, and position.

2. Air monitoring results are kept on file by EHS for duration of employment plus a

2.

(d)(3)

the workplace. Where the employer has monitored within one year prior to the effective date of this standard and the monitoring

or ot her ope rations f or w hich e ngineering a nd w ork-

sponsored by an appropriate governmental, academic or professional institution.

(i)(1)(iv) The employer shall assure that all examinations and procedures are provided without cost to the employee and at a reasonable time and place.

(i)(2) Initial examination.

(i)(2)(i) Within 60 days of the effective date of this standard, or before the time of initial assignment, the employer shall provide each employee covered by paragraph (i)(1)(i) of this section with a medical examination including the following elements:

(i)(2)(i)(A) A detailed occupational history which includes:

(i)(2)(i)(A)(1) Past work exposure to benzene or any other hematological toxins,

(i)(2)(i)(A)(2) A family history of blood dyscrasias including hematological neoplasms;

(i)(2)(i)(A)(3) A history of blood dyscrasias including genetic hemoglobin abnormalities, bleeding abnormalities, abnormal function of formed blood elements;

(i)(2)(i)(A)(4) A history of renal or liver dysfunction;

(i)(2)(i)(A)(5) A history of medicinal drugs routinely taken;

(i)(2)(i)(A)(6) A history of previous exposure to ionizing radiation and

(i)(2)(i)(A)(7) Exposure to marrow toxins outside of the current work situation.

(i)(2)(i)(B) A complete physical examination.

(i)(2)(i)(C) Laboratory tests.

(i)(5)(i)(A) The hemoglobin level or the hematocrit falls below the normal limit [outside the 95% confidence interval (C.I.)] as determined by the laboratory for the particular

(i)(6)(v) Information from previous employment-related medical

(j)(2)

(k)(2)(ii)(D) A copy of the information provided to the physician as required by paragraphs (i)(6)(ii) through (v) of this section; and

(k)(2)(ii)(E) A copy of the employee's medical and work history related to exposure to benzene or any other hematologic toxins.

(k)(2)(iii) The employer shall maintain this record for at least the duration of employment plus 30 years, in accordance with 29 CFR 1910.1020.

(k)(3) Availability.

(k)(3)(i) The employer shall assure that all records required to be

(k)(3)א i)employ¬ xposur£ᵐiwic𝑇 Þ

(l)(2) Observation procedures.

When obs ervation o f t he m easuring or m onitoring of employee exposure t o benzene r equires e ntry i nto a reas w here t he use of pr otective c lothing and equipment or respirators is required, the employer shall provide the observer with personal protective clothing and equipment or respirators required to be worn by employees working in the area, assure the use of such clothing and equipment or respirators, and require the observer to comply with all other applicable safety and health procedures.

(m) [Reserved]

(n) Appendices.

The information contained in Appendices A, B, C, and D is not intended, by itself, to create any additional obligations not otherwise imposed or m' l'l obl

OSHA Regulations (Standards - 29 CFR)
Substance safety data sheet, Benzene - 1910.1028 App A
Standard Number: 1910.1028 App A
Standard Title: Substance safety data sheet, Benzene
SubPart Number: Z
SubPart Title: Toxic and Hazardous Substances

I. Substance Identification

A. Substance: Benzene.

B. Permissible Exposure:

Except as to the use of gasoline, motor fuels and other fuels subsequent to discharge from bulk terminals and other exemptions specified in 1910.1028(a)(2):

1. Airborne:

The maximum time-weighted average (TWA) exposure limit is 1 part of benzene vapor per million parts of air (1 ppm) for an 8-hour workday and the maximum short-term exposure limit (STEL) is 5 ppm for any 15-minute period.

2. Dermal:

Eye contact shall be prevented and skin contact with liquid benzene shall be limited.

C. Appearance and odor:

Benzene is a clear, colorless liquid with a pleasant, sweet odor. The odor of benzene does not provide adequate warning of its hazard.

II. Health Hazard Data

A. Ways in which benzene affects your health.

Benzene can affect your health if you inhale it, or if it comes in contact with your skin or eyes. Benzene is also harmful if you happen to swallow it.

B. Effects of overexposure.

1. Short-term (acute) overexposure:

If you are overexposed to high concentrations of benzene, well above the levels where its odor is first recognizable, you may feel breathless, irritable, euphoric, or

B. Skin exposure.

If benzene is spilled on your clothing or skin, remove the contaminated clothing and wash the exposed skin with large amounts of water and soap immediately. Wash contaminated clothing before you wear it again.

C. Breathing.

If you or any other person breathes in large amounts of benzene, get the exposed person to fresh air at once. Apply artificial respiration if breathing has stopped. Call for medical assistance or a doctor as soon as possible. Never enter any vessel or confined space where the benzene concentration might be high without proper safety equipment and at least one other person present who will stay outside. A life line should be used.

D. Swallowing.

If benzene has been swallowed and the patient is conscious, do not induce vomiting. Call for medical assistance or a doctor immediately.

V. Medical Requirements

If you are exposed to benzene at a concentration at or above 0.5 ppm as an 8-hour time-

OSHA Regulations (Standards - 29 CFR)
Substance technical guidelines, Benzene - 1910.1028 App B
Standard Number: 1910.1028 App B
Standard Title: Substance technical guidelines, Benzene
SubPart Number: Z
SubPart Title: Toxic and Hazardous Substances

I. Physical and Chemical Data

A. Substance identification.

1. Synonyms:

Benzol, be nzole, c oal na phtha, c yclohexatriene, phe ne, phe nyl h ydride, pyrobenzol. (Benzin, petroleum benzin and Benzine do not contain benzene).

2. Formula: C(6)H(6) (CAS Registry Number: 71-43-2)

B. Physical data.

1. Boiling Point (760 mm Hg); 80.1 deg. C (176 deg. F)

2. Specific Gravity (water = 1): 0.879

3. Vapor Density (air = 1): 2.7

4. Melting Point: 5.5 deg. C (42 deg. F)

5. Vapor Pressure at 20 deg. C (68 deg. F): 75 mm Hg

6. Solubility in Water: .06%

7. Evaporation Rate (ether = 1): 2.8

8. Appearance and Odor: Clear, colorless liquid with a distinctive sweet odor.

II. Fire, Explosion, and Reactivity Hazard Data

A. Fire.

1. Flash Point (closed cup): - 11 deg. C (12 deg. F)

2. Autoignition Temperature: 580 deg. C (1076 deg. F)

3. Flammable limits in Air. % by Volume: Lower: 1.3%, Upper: 7.5%